



Sangoma EXP150 High-Performance LCD Expansion Module

Datasheet

Designed specifically for users who manage high call volumes, the Sangoma EXP150 expansion module delivers single-button access to contacts / extensions and maximizes productivity of the telephone attendant by efficiently dispatching inbound calls. The EXP150 is compatible with the Sangoma D65 series.



- ✓ Large 160x320 Graphic LCD Display
- ✓ 20 Programmable Hard Keys for up to 40 Programmable Features
- ✓ 2x Control Keys for Quickly Switching Pages

- ✓ Daisy-chain up to 6 Modules for up to 240 Programmable Keys
- ✓ Compatible with Sangoma D65 IP Phones
- ✓ 2x RJ45 Ports (1x Uplink & 1x Downlink)

Physical Features

The EXP150 features a large 160x320 graphic LCD display with 2 pages of 20 programmable hard keys delivering up to 40 programmable features. Dual-color LED and 2 control keys for fast page switching make the EXP150 simplify communications.

Expandability

Extend your investment by daisy-chaining up to 6 expansion modules for up to 240 programmable keys.

Call Features

Don't forget you can also program buttons for use with your favorite PhoneApps, which are all included with your Sangoma phone through the power of your FreePBX / PBXact PBX. These include:

- Call Hold
- Call Park
- Call Pick Up
- Redial
- Call Return
- Call Forward
- Call Transfer
- Caller ID Display
- Do Not Disturb
- Conference Rooms
- Speed Dial
- Voicemail
- Shared Line
- BLF

Technical Specifications

PSTN Protocols

- ⦿ 160x320 graphic LCD with 16-level grayscales
- ⦿ LCD backlight
- ⦿ Two page views are possible
- ⦿ Different icons for each function shown on the LCD
- ⦿ Local GUI controlled by host Sangoma D65 phone

Feature Keys

- ⦿ 20x physical keys each with a dual-color LED
- ⦿ 2x independent control keys
- ⦿ Daisy-chain up to 6 modules for up to 240 programmable keys

Certification

- ⦿ EMC: FCC Part 15 Class B, EN 55022, EN 55024, EN 61000
- ⦿ Safety: EN 60950

Connectivity

- ⦿ 2x RJ45 ports (1x uplink and 1x downlink)

Environmental

- ⦿ Operating humidity: 10~95%
- ⦿ Operating temperature: -10~50°C

Dimensions

Box Size

- ⦿ 140mm (W) x 251mm (D) x 91mm (H)

Shipping Weight

- ⦿ 1.18kgs (2.6lbs)

Power

- ⦿ External Type A AC adapter *Included
 - AC 100~240V input
 - DC 5V/1.2A output

